

HDBaseT технология передачи сигналов

# 3-канальный приемник HDBaseT с выходами HDMI

## HBT-30

|                        |                                                                                                                                                                        |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video/Audio Input      | HDBaseT (RJ-45) x 3<br>Cable Type: Cat6A shielded                                                                                                                      |
| Video/Audio Output     | HDMI 2.0 x 3                                                                                                                                                           |
| Supported Video Format | 3840x2160p: 60/59.94/50/30/29.97/25/24/23.98<br>1080p: 60/59.94/50/30/29.97/25/24/23.98<br>1080i: 60/59.94/50<br>720p: 60/59.94/50<br>525i: 59.94 NTSC<br>625i: 50 PAL |
| Video Process          | 4K60 4:4:4, 8bit<br>4K60 4:2:2 10bit<br>4K60 4:2:0 10bit                                                                                                               |
| Video bandwidth        | Single-link 594MHz [18Gbps]                                                                                                                                            |
| DVIP                   | RJ-45 x1(input)                                                                                                                                                        |
| RS-422/ RS-232         | RJ-45 x 3 (RS-232/RS-422)                                                                                                                                              |
| Power                  | DC IN: DC 56V                                                                                                                                                          |
| PoE Output             | 65W per channel                                                                                                                                                        |
| HDBaseT Distance       | 1080p@60 up to 100M by CAT. 6A cable<br>4K@60 up to 100M by CAT. 6A cable                                                                                              |
| HDMI compliance        | HDMI Deep Color & 4K@60                                                                                                                                                |
| HDCP compliance        | HDCP 2.2/1.4 (Bypass)                                                                                                                                                  |
| Audio support          | Surround Sound [up to 7.1 Channel) or Stereo Digital Audio                                                                                                             |
| Dimension (LxWxH)      | 440 x 125 x 44.5 mm                                                                                                                                                    |
| Weight                 | 1.8Kg                                                                                                                                                                  |
| Operating Temp. Range  | 0~40 °C                                                                                                                                                                |
| What's in the Box      | 1 x HBT-30 main unit<br>1 x AC cord<br>1 x DC 56V power adaptor                                                                                                        |